Organisme certificateur

Certificat

Système de traitement des joints entre plaques de plâtre
Cloisons, plafonds et liaisons

PLATEC ™ : Traitement des joints entre plaques de plâtre à bords amincis ou biseautés - Enduit mixte -Type 3B - prise, enduit en poudre.

Sans ou avec bande à joint SINIAT : Bandes à joint papier associées - marquage SI.

Le CSTB atteste que le système ci-dessus est conforme à des caractéristiques décrites dans le référentiel de certification QB 06 « Système de traitement des joints entre plaques de plâtre » en vigueur après évaluation selon les modalités de contrôle définies dans ce référentiel.

En vertu de la présente décision, le CSTB accorde à :

La société **Etex France Building Performance**
500 Rue Marcel Demonque – FR - 84915 AVIGNON CEDEX 9

Usine **Etex France Building Performance - MERIEL**
FR - 95630 MERIEL

Le droit d'usage de la marque QB 06 « Système de traitement des joints entre plaques de plâtre » pour le produit objet de cette décision, pour toute sa durée de validité et dans les conditions prévues par les exigences générales de la marque QB et le référentiel mentionné ci-dessus.

62-10-863

Décision de reconduction n°425 - 62-10-863 du 12/12/2019
Cette décision se substitue à la décision de reconduction n°424 - 62-10-863 du 19/09/2018
Sauf retrait, suspension, ou modification, ce certificat est valable jusqu'au 19/03/2021.
Le certificat en vigueur peut être consulté sur le site internet http://evaluation.cstb.fr pour en vérifier sa validité.

CARACTÉRISTIQUES CERTIFIÉES

Avec un niveau de performance plus exigeant que la norme NF EN 13963 (usage courant)

Comportement à sec :

- Efficacité du collage de la bande ≥ 1000g
- Résistance à la fissuration : Pas de fissuration pour une épaisseur ≤ à 1,5 mm

Référence usage élargi AT ou DTA n°: 9/14-984

Ce certificat comporte 1 page.
Correspondant :
Karima BOUSLAMA
Courriel : **contacts-QB06@cstb.fr**
Tél. : 01 64 68 82 49

Pour le CSTB
Pour le Président

Edwige PARISEL

CENTRE SCIENTIFIQUE ET TECHNIQUE DU BÂTIMENT
84 avenue Jean Jaurès – Champs-sur-Marne – 77447 Marne-la-Vallée cedex 2
Tél. : +33 (0)1 64 68 82 82 – Fax : +33 (0)1 64 68 89 94 – www.cstb.fr
MARNE-LA-VALLÉE / PARIS / GRENOBLE / NANTES / SOPHIA ANTIPOLIS

cofrac
ACCREDITATION N° 5-0010 Scope available on / Portée disponible sur WWW.COFRAC.FR
CERTIFICATION DE PRODUITS ET SERVICES

CSTB le futur en construction

Certification body

Certificate

Joint treatment system for plasterboard
Distribution partition, wall lining and suspended celing

PLATEC ™ : Joint treatment between plasterboard with tapered edges beveled - dual-purpose compound - Type 3B - setting, powder compound

Without or with Paper tape SINIAT: Associated paper tape - marking SI

CSTB hereby certifies that the above-mentioned product complies with the characteristics described in the certification reference system QB 06 Joint treatment system for plasterboard in force, following an assessment performed according to the inspection procedures set out in this reference system.

By virtue of the present decision, CSTB grants:

The Company	**Etex France Building Performance** **500 Rue Marcel Demonque – FR - 84915 AVIGNON CEDEX 9– France**
Plant	**Etex France Building Performance - MERIEL** **FR - 95630 MERIEL**

the right to use the QB 06-mark Joint treatment system for plasterboard for the product covered under this decision, throughout its period of validity and under the conditions stipulated under the general requirements of the QB mark and the above-mentioned reference system.

62-10-863

Decision of renewal no.425 -62-10-863 of 12/12/2019
This decision takes the place of the decision of renewal no. 424-62-10-863 of 19/09/2018
Unless withdrawn, suspended or modified, this certificate is valid until 19/03/2021
This valid certificate may be watched on the following web site http://evaluation.cstb.fr to check its validity.

CERTIFIED CHARACTERISTICS

With a level of performance more demanding than standard NF EN 13963 (current use)

Dry behavior:

- Efficient adhesion of the tape ≥ 1000 g
- Resistance to cracking: No cracking for a thickness ≤ 1,5 mm

Extended Usage specifications AT or DTA no 9/14-984

This certificate has 1 page.
Contact :
Karima BOUSLAMA
Email : **contacts-QB06@cstb.fr**
Phone : +33 1 64 68 82 49

For CSTB
On behalf of the President

Edwige PARISEL

cofrac
ACCREDITATION N° 5-0010 Scope available on / Portée disponible sur WWW.COFRAC.FR
CERTIFICATION DE PRODUITS ET SERVICES