

# Certificate

Sanitary components

**Family of products: WATER**

CSTB hereby certifies that the products referred to in the appendix comply with the characteristics described in the certification reference system Sanitary components (NF 076), in force, following an assessment performed according to the inspection procedures set out in this reference system.

By virtue of the present decision notified by CSTB, AFNOR Certification grants:

**The company**            **IDEAL STANDARD France**  
                                 **PARIS NORD II - Parc des Reflets**  
                                 **165 avenue du Bois de la Pie**  
                                 **FR-95920 ROISSY CDG CEDEX**  
**Factory :**                **FR-16160 GOND PONTOUVRE**

the right to use the NF mark Sanitary components for the products covered under this decision, throughout its period of validity and under the conditions provided for in the general rules of NF mark and the above-mentioned reference system.

Decision of renewal n° 252-U1-19/2 dated of 12/09/2019  
This decision cancels and replaces decision n° 252-U1-19/1 dated of 04/03/2019

Except in case of withdrawal, suspension or modification, this certificate is valid for 15 months.  
This valid certificate is available on the following Web site <http://evaluation.cstb.fr> to check its validity.

## CERTIFIED CHARACTERISTICS

The products covered by the NF mark Sanitary components have the minimal characteristics required by the standards, possibly completed by the technical specifications specified in the appendix

**This certificate comprises 3 pages.**

**Correspondent :**  
Stéphane FATIS  
Phone : (33) 01 64 68 88 60  
Fax : (33) 01 64 68 84 44  
Email : stephane.fatis@cstb.fr

For CSTB  
On behalf of the President



Edwige PARISEL

**Appendix to the Certificate**

Decision no. 252-U1-19/2

**INLET VALVE**

These products have the minimum characteristics defined in the NF EN 14-124 standard and in the technical documents DT076-01 and DT076-02.

CSTB	Trademark	Range	Reference	DN	Class Acou.	Lap	qm	Type of supply
<b>INLET VALVE</b>								
F01a)	IDEAL STANDARD	--	RR661940	3/8	II	23	0,18	SIDE SUPPLY
F01a)	IDEAL STANDARD	--	D6701BG	3/8	II	23	0,18	SIDE SUPPLY
F01a)	IDEAL STANDARD	--	RR662990	3/8	II	23	0,18	SIDE SUPPLY
F01a)	IDEAL STANDARD	--	RR661899	3/8	II	23	0,18	SIDE SUPPLY
F01a)	IDEAL STANDARD	--	RR 661990	3/8	II	23	0,18	SIDE SUPPLY
F01a)	IDEAL STANDARD	--	R7585BG	3/8	II	23	0,18	SIDE SUPPLY
F01a)	IDEAL STANDARD	--	R7582BG	3/8	II	23	0,18	SIDE SUPPLY
F01a)	IDEAL STANDARD	--	R6589BG	3/8	II	23	0,18	SIDE SUPPLY
F01a)	IDEAL STANDARD	--	R6579BG	3/8	II	23	0,18	SIDE SUPPLY
F01a)	IDEAL STANDARD	--	R6009BG	3/8	II	23	0,18	SIDE SUPPLY
F01a)	IDEAL STANDARD	--	R6512BG	3/8	II	23	0,18	SIDE SUPPLY
F01b)	IDEAL STANDARD	--	R6513BG	3/8	I	18	0,19	BOTTOM SUPPLY
F01b)	IDEAL STANDARD	--	R6507BG	3/8	I	18	0,19	BOTTOM SUPPLY
F01b)	IDEAL STANDARD	--	R6008BG	3/8	I	18	0,19	BOTTOM SUPPLY
F01b)	IDEAL STANDARD	--	D6700BG	3/8	I	18	0,19	BOTTOM SUPPLY
F01b)	IDEAL STANDARD	--	RR661899	3/8	I	18	0,19	BOTTOM SUPPLY
F01b)	IDEAL STANDARD	--	RR661890	3/8	I	18	0,19	BOTTOM SUPPLY
F01b)	IDEAL STANDARD	--	RR661840	3/8	I	18	0,19	BOTTOM SUPPLY
F01b)	IDEAL STANDARD	--	R7586BG	3/8	I	18	0,19	BOTTOM SUPPLY
F01b)	IDEAL STANDARD	--	R6588BG	3/8	I	18	0,19	BOTTOM SUPPLY
F01b)	IDEAL STANDARD	--	R6580BG	3/8	I	18	0,19	BOTTOM SUPPLY
F01c)	IDEAL STANDARD	--	RR661944	3/8	I	18	0,19	SIDE SUPPLY
F02	IDEAL STANDARD	--	AQUAFLEX LAT OD	3/8	II	23	0,19	SIDE SUPPLY

**FLUSHING MECHANISMS**

These products have the minimum characteristics defined in the technical documents DT076-01 and DT076-03.

CSTB	Trademark	Range	Reference	Type	Cover boring	Flush volume (l)	Residual regulation	hmax	hmin
<b>UNIVERSAL MECHANISM</b>									
I01a)	IDEAL STANDARD	--	R6000AA	Poussoir	--	6	No	--	--
I01a)	IDEAL STANDARD	--	R6540AA	Poussoir	--	6	No	--	--
I01a)	IDEAL STANDARD	--	R6586AA	Poussoir	--	6	No	--	--
I01a)	IDEAL STANDARD	--	R7632AA	Poussoir	--	6	No	--	--
I01a)	IDEAL STANDARD	--	RR601291	Poussoir	--	6	No	--	--
I01a)	IDEAL STANDARD	--	RR647901	Poussoir	--	6	No	--	--
I01a)	IDEAL STANDARD	--	R7583AA	Poussoir	--	6	No	--	--
I01a)	IDEAL STANDARD	--	D6502AA	Poussoir	--	6	No	--	--
<b>UNIVERSAL WATER SAVING MECHANISM</b>									
K01	IDEAL STANDARD	--	R6587AA	Poussoir	--	3/6 - 9/4	No	--	--
K01	IDEAL STANDARD	--	R6002AA	Poussoir	--	3/6 - 9/4	No	--	--
K01	IDEAL STANDARD	--	R6578AA	Poussoir	--	3/6 - 9/4	No	--	--
K01	IDEAL STANDARD	--	R7580AA	Poussoir	--	3/6 - 9/4	No	--	--
K01	IDEAL STANDARD	--	R7588AA	Poussoir	--	3/6 - 9/4	No	--	--
K01	IDEAL STANDARD	--	R7633AA	Poussoir	--	3/6 - 9/4	No	--	--
K01	IDEAL STANDARD	--	RR601295	Poussoir	--	3/6 - 9/4	No	--	--
K01	IDEAL STANDARD	--	R6540AA	Poussoir	--	3/6 - 9/4	No	--	--
K01	IDEAL STANDARD	--	D6503AA	Poussoir	--	3/6 - 9/4	No	--	--

**Appendix to the Certificate**

Decision no. 252-U1-19/2

**BOTH INLET VALVE + MECHANISM**

SFAM	CSTB	Trademark	Range	Reference	Type	combinaison	Residual regulation	hmax	hmin
RF+MEC	G04	IDEAL STANDARD	--	R6555AA		F01a) + K01	No	--	--
RF+MEC	G04	IDEAL STANDARD	--	R6504AA		F01a) + K01	No	--	--
RF+MEC	G06	IDEAL STANDARD	--	R6554AA		F01b) +K01)	No	--	--
RF+MEC	G06	IDEAL STANDARD	--	R6504AA		F01b) +K01)	No	--	--