

Certificat

Revêtements de sol résilients

TX TECHCONFORT EVO

Le CSTB atteste que le produit ci-dessus est conforme à des caractéristiques décrites dans le référentiel de certification « Revêtements de sol résilients » (QB 30) en vigueur après évaluation selon les modalités de contrôle définies dans ce référentiel.

En vertu de la présente décision, le CSTB accorde à :

La société **NUANCES UNIKALO**
18 rue du Meilleur Ouvrier de France
Z.I. de l'Hippodrome
FR - 33700 MERIGNAC
Usine 347

le droit d'usage de la marque QB associée au classement UPEC – « Revêtements de sol résilients », pour le produit objet de cette décision, pour toute sa durée de validité et dans les conditions prévues par les exigences générales de la marque QB et le référentiel mentionné ci-dessus.



Décision d'admission n° 771/347-003.1_00/21 du 23 novembre 2021

Sauf retrait, suspension, ou modification, ce certificat est valide.

Le certificat en vigueur peut être consulté sur le site internet <http://evaluation.cstb.fr> pour en vérifier sa validité.

CARACTÉRISTIQUES CERTIFIÉES

> Selon la norme NF EN ISO 26986 - Revêtements de sol amortis à base de polychlorure de vinyle expansé :

Largeur des rouleaux (mm)	2000 ; 3000 ; 4000 (-0)
Épaisseur totale (mm)	2,60 (+ 0,18 - 0,15)
Épaisseur de la couche d'usure (mm)	0,25 (+ 13% - 10% limité à ± 0,1 mm)
Masse surfacique totale (g/m ²)	1 800 (+ 13% - 10%)

> Autres caractéristiques :

Groupe d'abrasion T

> Performances acoustiques (NF EN ISO 717/2 et NF S 31-074) :

Efficacité acoustique au bruit de choc : $\Delta L_w = 19$ dB
Sonorité à la marche : classe A ($L_{new} < 65$ dB)

Ce certificat comporte 1 page.

Correspondant :
Agathe MENAY
Courriel : agathe.menay@cstb.fr
Tél. : 01 64 68 83 96

A ce certificat QB est attaché le classement UPEC suivant :

Nature du support	Pose lés	Classement			
		U	P	E	C
Chape ciment ou béton	(b ou c)/d	2s	2	2/3	2
Bois ou à base de bois	(b ou c)/d	2s	2	1/3	2

a = joints vifs

c = joints soudés à chaud

b = joints traités à froid

d = c + étanchéité en rives

Par délégalion
du Président

Florian RASSE

Certificate

Resilient floor coverings

TX TECHCONFORT EVO

CSTB hereby certifies that the above-mentioned product complies with the characteristics described in the certification reference system "Resilient floor coverings" (QB 30) in force, following an assessment performed according to the inspection procedures set out in this reference system.

By virtue of the present decision, CSTB grants:

The Company **NUANCES UNIKALO**
18 rue du Meilleur Ouvrier de France
Z.I. de l'Hippodrome
FR - 33700 MERIGNAC
347

Plant

the right to use the QB mark associated with UPEC classification – "Resilient floor coverings", for the product covered under this decision, throughout its period of validity and under the conditions stipulated under the general requirements of the QB mark and the above-mentioned reference system.



Admission decision n° 771/347-003.1_00/21, on November 23rd 2021

Except in case of withdrawal, suspension or modification, this certificate is valid.

This valid certificate may be watched on the following web site <http://evaluation.cstb.fr> to check its validity.

CERTIFIED CHARACTERISTICS

> As per Standard NF EN ISO 26986 - Expanded (cushioned) polyvinyl chloride floorcovering:

Roll width (mm)	2000 ; 3000 ; 4000 (-0)
Total thickness (mm)	2,60 (+ 0,18 - 0,15)
Wear layer thickness (mm)	0,25 (+ 13% - 10% limited to ± 0,1 mm)
Total mass per unit area (g/m ²)	1 800 (+ 13% - 10%)

> Other characteristics:

Wear group T

> Acoustic performances (NF EN ISO 717/2 and NF S 31-074):

Impact sound insulation: $\Delta L_w = 19$ dB
Walk noise: class A ($L_{new} < 65$ dB)

This certificate comprises 1 page.

Contact:
Agathe MENAY
Email: agathe.menay@cstb.fr
Phone: 01 64 68 83 96

The following classification UPEC is associated with this QB Certificate:

Subfloor type	Roll installation	Classification			
		U	P	E	C
Cement or concrete	(b or c)/d	2s	2	2/3	2
Wood or wooden	(b or c)/d	2s	2	1/3	2

a = un-welded joints
c = hot welded joints

b = cold welded joints
d = c + watertight edges

For CSTB
On behalf of the President

Florian RASSE