

Certificat de constance des performances du produit **0679-CPR-1297**

(Version originale en langue française)

Dans le cadre du règlement (UE) n°305/2011 du Parlement Européen et du Conseil du 9 mars 2011, établissant des conditions harmonisées de commercialisation pour les produits de construction et abrogeant la Directive 89/106/CEE du Conseil, il a été établi que le(s) produit(s) de construction désigné(s) dans la page suivante, mis sur le marché de la zone économique européenne par :

KNAUF SASZone d'activités
68600 WOLFGANTZEN
France

et fabriqué(s) dans l'usine :

**KNAUF FIBRE
LA COTE (70)**

est (sont) soumis par le fabricant à un contrôle de la production en usine ainsi qu'à des essais complémentaires d'échantillons prélevés dans l'usine conformément au plan d'essais prescrit, et que le CSTB, organisme notifié, a réalisé l'évaluation de la performance de réaction au feu du (des) produit(s) de construction, l'inspection initiale de l'établissement de fabrication et du contrôle de la production en usine, et réalise une surveillance, une évaluation et une appréciation continues du contrôle de la production en usine (système 1).

Ce certificat atteste la performance de réaction au feu du (des) produit(s) et que toutes les dispositions concernant l'évaluation et la vérification de la constance de cette performance décrites dans la spécification technique harmonisée de référence :

EN 13964 : 2014

Performance de réaction au feu du produit B-s1, d0

sont appliquées et que le(s) produit(s) satisfait(ont) à toutes les exigences prescrites.


Quiconque présente ce certificat doit également produire in extenso la déclaration des performances du produit établie par le fabricant, ou son représentant désigné établi dans la zone économique européenne, et la spécification technique de référence.

Ce certificat est délivré le 16/06/2022, il se substitue au certificat précédemment délivré le 25/05/2022 et, sauf retrait ou suspension, demeure valide tant que les conditions précisées dans la spécification technique de référence ou les conditions de fabrication en usine ou le contrôle de la production en usine ne sont pas modifiés de manière significative.

Ce certificat comporte 2 pages.

La liste des certificats délivrés par le CSTB est tenue à jour au CSTB.

Délivré à Champs sur Marne, le 16/06/2022.

Par délégation
du Président

Florian RASSE

Certificat de constance des performances du produit **0679-CPR-1297****ORGANIC MINERAL - ORGANIC MINERAL AUTHENTIC - ORGANIC TWIN – ORGANIC TWIN AUTHENTIC - ORGANIC MINERAL COLORS - ORGANIC MINERAL AUTHENTIC COLORS - ORGANIC TWIN COLORS - ORGANIC TWIN AUTHENTIC COLORS**Description du produit :

Panneaux pour usage en plafond suspendu constitués de parements en laine de bois et d'une âme en laine de roche contrecollée. Les panneaux présentent un parement de laine de bois sur une face ou sur les 2 faces.

Coloris des panneaux non peints : gris ou beige

Coloris des panneaux peints (finition COLORS) : divers

Performance du produit de construction :

Nom des produits	Couleurs	Epaisseur (mm)	Réaction au feu / Euroclasse
ORGANIC MINERAL - ORGANIC MINERAL AUTHENTIC	Gris ou Beige	25 à 360 mm	B-s1, d0
ORGANIC TWIN – ORGANIC TWIN AUTHENTIC	Gris ou Beige	25 à 360 mm	B-s1, d0
ORGANIC MINERAL COLORS - ORGANIC MINERAL AUTHENTIC COLORS	Divers	25 à 360 mm	B-s1, d0
ORGANIC TWIN COLORS - ORGANIC TWIN AUTHENTIC COLORS	Divers	25 à 360 mm	B-s1, d0

Catégorie d'utilisation :

Plafonds suspendus - Eléments d'habillage de plafond

Conditions particulières pour l'utilisation du produit :

Sans substrat ou sur tout substrat de masse volumique ≥ 820 kg/m³ classé A1 ou A2-s1,d0.

Avec ou sans lame d'air.

Certificate of constancy of the performance of the product **0679-CPR-1297**

(English translation, the original version is in French)

In compliance with the Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 laying down harmonised conditions for the marketing of construction products and repealing Council Directive 89/106/EEC, it has been stated that the construction products indicated in the following page, placed on the European economic area market by:

KNAUF SAS

Zone d'activités
68600 WOLFGANTZEN
France

and produced in the factory:

**KNAUF FIBRE
LA COTE (70)**

is (are) submitted by the manufacturer to a factory production control and to the further testing of samples taken of the factory in accordance with a prescribed test plan, and that the notified body - CSTB - has performed the assessment of the reaction to fire performance of the construction product(s), the initial inspection of the manufacturing plant and of the factory production control and performs the continuing surveillance, assessment and evaluation of the factory production control (system 1).

This certificate attests the reaction to fire performance of the product(s) and that all provisions concerning the assessment and verification of constancy of performance described in the harmonized reference technical specification:

EN 13964 : 2014

Product reaction to fire performance: B-s1, d0

are applied and that the product(s) fulfills (fulfill) all the prescribed requirements.

This certificate can only be used in conjunction with the declaration of performance of the product written by the manufacturer or his authorised representative established in the European economic area and with the technical specification in reference.

This certificate is issued on 6/16/2022, it replaces the certificate previously delivered on 5/25/2022 and, except for withdrawal or suspension, remains valid as long as the conditions laid down in the corresponding technical specification in reference or the manufacturing conditions in the factory or the factory production control itself are not modified significantly.

This certificat comprises 2 pages.

The list of certificates issued by CSTB is kept up-to-date by the CSTB.

Issued in Champs sur Marne, on 6/16/2022.

For CSTB
On behalf of the President



Florian RASSE

Certificate of constancy of the performance of the product **0679-CPR-1297****ORGANIC MINERAL - ORGANIC MINERAL AUTHENTIC -ORGANIC TWIN – ORGANIC TWIN AUTHENTIC -ORGANIC MINERAL COLORS - ORGANIC MINERAL AUTHENTIC COLORS -ORGANIC TWIN COLORS - ORGANIC TWIN AUTHENTIC COLORS**Product description:

Panels for suspended ceiling application made of wood wool siding and a laminated rock wool core.
Panels have wood wool siding on one or both sides

Colours of unpainted panels : Grey or beige.

Colours of painted panels (ICOLORS finish) : Various.

Performance of the construction product:

Products name	Colors	Thickness (mm)	Reaction to Fire / Euroclass
ORGANIC MINERAL - ORGANIC MINERAL AUTHENTIC	Grey or Brige	25 à 360 mm	B-s1, d0
ORGANIC TWIN – ORGANIC TWIN AUTHENTIC	Grey or Brige	25 à 360 mm	B-s1, d0
ORGANIC MINERAL COLORS - ORGANIC MINERAL AUTHENTIC COLORS	Various	25 à 360 mm	B-s1, d0
ORGANIC TWIN COLORS - ORGANIC TWIN AUTHENTIC COLORS	Various	25 à 360 mm	B-s1, d0

Use category:

Suspended ceiling - ceiling membrane components

Particular conditions applicable to the use of the product:

Without substrate or any A1 or A2-s1,d0 substrate with a density ≥ 820 kg/m3.

With or without air gap