

Authorized and notified according to article 39 of Regulation (EU) N°305/2011 of the European Parliament and of the Council of 9 March 2011 laying down harmonized conditions for the marketing of construction products

Certificate of constancy of the performance of the product

0679-CPR-0921

(English translation, the original version is in French)

In compliance with the Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 laying down harmonised conditions for the marketing of construction products and repealing Council Directive 89/106/EEC, it has been stated that the construction products indicated in the following page, placed on the European economic area market by:

ZOLPAN S.A.S

17, quai Joseph Gillet FR-69316 LYON CEDEX 4

and produced in the factory:

ZOLPAN S.A.S - Le Gunin CD 921 - BP 4 - FR-73520 LA BRIDOIRE

is submitted by the manufacturer to a factory production control and to the further testing of samples taken of the factory in accordance with a prescribed test plan, and that the notified body - CSTB - has performed the assessment of the performance of the construction product, the initial inspection of the manufacturing plant and of the factory production control and performs the continuing surveillance, assessment and evaluation of the factory production control (system 1).

This certificate attests to the product performance, relative to the fire reaction performance chosen by the manufacturer, and that all provisions concerning the assessment and verification of constancy of this performance described in the harmonised reference technical specification:

European Technical Approval Guideline No 004 (ETAG 004), edition 2013 used as European Assessment Document (EAD) completed by :

European Technical Assessment ETA-12/0134 - version 1, delivered 2nd March 2016

are applied and that the product fulfill all the prescribed requirements.


This certificate can only be used in conjunction with the declaration of performance of the product written by the manufacturer or his authorised representative established in the European economic area and with the technical specification in reference.

This certificate is issued on 29th November 2022, it replaces the certificate previously delivered on 4th October 2018 and, except for withdrawal or suspension, remains valid as long as the conditions laid down in the corresponding technical specification in reference or the manufacturing conditions in the factory or the factory production control itself are not modified significantly.

This certificat comprises 3 pages.

The list of certificates issued by CSTB is kept up-to-date by the CSTB.

Issued in Champs sur Marne, on 29th November 2022.







Authorized
and notified according
to article 39 of

Regulation (EU) N°305/2011
of the European Parliament
and of the Council
of 9 March 2011 laying down
harmonized conditions
for the marketling
of construction products

Certificate of constancy of the performance of the product

0679-CPR-0921

ARMATERM SC PSE

External Thermal Insulation Composite System with paste render (ETICS)

Product fire reaction performance:

B-s2,d0, according to the standard EN 13501-1+A1: 2013

only valid for the following configurations:

| Configuration | Declared | Declared | Class |
|---|--|---|--------------|
| | organic | flame retardant | according to |
| | content ⁽¹⁾ | content ⁽¹⁾ | EN 13501-1 |
| Adhesives: - ARMATERM COLLE - ARMATERM COLLE 3C - ARMATERM COLLE 3C+ - ARMATERM COLLE POUDRE - ARMATERM GC - ARMATERM QUICK FIX PU Insulation product: EPS panels, Euroclass E, thickness ≤ 300 mm, density ≤ 20 kg/m³ Base coat: ARMENDUIT FX • Mesh: - R 131 A 101 C+ - R 131 A 102 C+ - SSA-1363 F+ Key coat: ARMAFOND Finishing coats: - ARMATERM 101 FX - ARMATERM 201 FX - ARMATERM 202 FX - ARMATERM 301 FX - ARMATERM 401 FX - ARMATERM 401 FX - ARMATERM 0.35 - SILEXTRA TALOCHÉ FX - SILEXTRA RIBBÉ FX - ZOLGRANIT GF - ZOLGRANIT GM | Base coat: 8.8% Key coat: 13.3% Finishing coats: 7.3 to 14.6% | Base coat: 18.1% Key coat: 0.0% Finishing coats: ≤ 18.3% | B-s2,d0 |

⁽¹⁾ Percentage declared by the Manufacturer, relative to the dried weight of the component as delivered.

<u>Use category</u>: External insulation of buildings' walls

<u>Particular conditions applicable to the use of the product</u>:

Application on vertical walls of masonry or concrete