

**Certificate** of constancy of the performance of the product**0679-CPR-1045**

(English translation, the original version is in French)

In compliance with the Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 laying down harmonised conditions for the marketing of construction products and repealing Council Directive 89/106/EEC, it has been stated that the construction products indicated in the following page, placed on the European economic area market by:

**PLASDOX PEINTURES**71, boulevard du Général Leclerc  
FR-92593 CLICHY CEDEX

and produced in the factory:

**292**

is submitted by the manufacturer to a factory production control and to the further testing of samples taken of the factory in accordance with a prescribed test plan, and that the notified body - CSTB - has performed the assessment of the performance of the construction product, the initial inspection of the manufacturing plant and of the factory production control and performs the continuing surveillance, assessment and evaluation of the factory production control (system 1).

This certificate attests to the product performance, relative to the fire reaction performance chosen by the manufacturer, and that all provisions concerning the assessment and verification of constancy of this performance described in the harmonised reference technical specification:

European Technical Approval Guideline No 004 (ETAG 004), edition 2013  
used as European Assessment Document (EAD)

completed by

European Technical Assessment ETA-09/0049 – version 2, delivered 15th February 2018

are applied and that the product fulfill all the prescribed requirements.

This certificate can only be used in conjunction with the declaration of performance of the product written by the manufacturer or his authorised representative established in the European economic area and with the technical specification in reference.

This certificate is issued on 29<sup>th</sup> November 2022, it replaces the certificate previously delivered on 02<sup>nd</sup> October 2018 and, except for withdrawal or suspension, remains valid as long as the conditions laid down in the corresponding technical specification in reference or the manufacturing conditions in the factory or the factory production control itself are not modified significantly.

This certificat comprises 2 pages.

The list of certificates issued by CSTB is kept up-to-date by the CSTB.

Issued in Champs sur Marne, on 29<sup>th</sup> November 2022.Par délégation  
du Président

Florian RASSE

**PARA-THERM TRADI**

**External Thermal Insulation Composite System with powder render (ETICS)**

Product fire reaction performance:

**B – s2, d0, according to the standard EN 13501-1+A1 : 2013**

only valid for the following configurations :

Configuration	Declared organic content <sup>(1)</sup>	Declared flame retardant content <sup>(1)</sup>	Class according to EN 13501-1
<ul style="list-style-type: none"> <li>• Adhesives / supplementary adhesives:               <ul style="list-style-type: none"> <li>- PARA-THERM CIMENT CSE</li> <li>- PARA-THERM POUDRE 3C</li> <li>- PARA-THERM POUDRE 3C+</li> <li>- PARA-THERM POUDRE CSE</li> <li>- PARA-THERM POUDRE GC</li> <li>- MOUSSE PU COLLAGE ISOLANTS CROMOLOGY SERVICES</li> </ul> </li> <li>• Insulation product: EPS boards, reaction to fire Class E, thickness ≤ 300 mm, density ≤ 20 kg/m<sup>3</sup></li> <li>• Base coat:               <ul style="list-style-type: none"> <li>- PARA-THERM POUDRE CSE</li> </ul> </li> <li>• Meshes:               <ul style="list-style-type: none"> <li>- R 131 A 101 C+</li> <li>- R 131 A 102 C+</li> <li>- SSA 1363 F+</li> </ul> </li> <li>• Key coats (if necessary):               <ul style="list-style-type: none"> <li>- PARA-THERM RÉGUL</li> <li>- SILIPRIMER</li> </ul> </li> <li>• Finishing coats:               <ul style="list-style-type: none"> <li>- PARA-THERM CF TALOCHÉ XF</li> <li>- PARA-THERM CF RIBBÉ G</li> <li>- PARA-THERM CF RIBBÉ M</li> <li>- PARA-THERM CF TALOCHÉ M</li> <li>- PARA-THERM CF TALOCHÉ G</li> <li>- PARA-THERM CF ROULÉ</li> <li>- PARA-THERM CF SILOXANE TALOCHÉ</li> <li>- SILISETTEF OT FIN</li> <li>- SILISETTEF L</li> </ul> </li> </ul>	<p style="text-align: center;">Base coat: 7.0%</p> <p style="text-align: center;">Finishing coats: 6.8 to 14.7%</p>	<p style="text-align: center;">Base coat: 0.0%</p> <p style="text-align: center;">Finishing coats: 0.0 to 18.3%</p>	B – s2, d0

<sup>(1)</sup> Percentage declared by the Manufacturer, relative to the dried weight of the component as delivered.

Use category:

External insulation of buildings' walls

Particular conditions applicable to the use of the product:

Application on vertical walls of masonry or concrete