

Authorized
and notified according
to article 39 of
Regulation (EU) N°305/2011
of the European Parliament
and of the Council
of 9 March 2011 laying down
harmonized conditions
for the marketing
of construction products
the state of the council of t

Certificate of constancy of the performance of the product

0679-CPR-1247

(English translation, the original version is in French)

In compliance with the Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 laying down harmonised conditions for the marketing of construction products and repealing Council Directive 89/106/EEC, it has been stated that the construction products indicated in the following page, placed on the European economic area market by:

PLASDOX PEINTURES

71, boulevard du Général Leclerc FR-92593 CLICHY CEDEX

and produced in the factory:

292

is submitted by the manufacturer to a factory production control and to the further testing of samples taken of the factory in accordance with a prescribed test plan, and that the notified body - CSTB - has performed the assessment of the performance of the construction product, the initial inspection of the manufacturing plant and of the factory production control and performs the continuing surveillance, assessment and evaluation of the factory production control (system 1).

This certificate attests to the product performance, relative to the fire reaction performance chosen by the manufacturer, and that all provisions concerning the assessment and verification of constancy of this performance described in the harmonised reference technical specification:

European Technical Approval Guideline No 004 (ETAG 004), edition 2013 used as European Assessment Document (EAD)

completed by

European Technical Assessment ETA-12/0613 - version 1, delivered 14th December 2016

are applied and that the product fulfill all the prescribed requirements.


This certificate can only be used in conjunction with the declaration of performance of the product written by the manufacturer or his authorised representative established in the European economic area and with the technical specification in reference.

This certificate is issued on 28th November 2022, it replaces the certificate previously delivered on 04th October 2018 and, except for withdrawal or suspension, remains valid as long as the conditions laid down in the corresponding technical specification in reference or the manufacturing conditions in the factory or the factory production control itself are not modified significantly.

This certificat comprises 2 pages.

The list of certificates issued by CSTB is kept up-to-date by the CSTB.

Issued in Champs sur Marne, on 28st November 2022.







Authorized
and notified according
to article 39 of
Regulation (EU) N°305/2011
of the European Parliament
and of the Council
of 9 March 2011 laying down
harmonized conditions
for the marketing
of construction products

Certificate of constancy of the performance of the product

0679-CPR-1247

PARA-THERM EASY 2.0

External Thermal Insulation Composite System with paste render (ETICS)

Product fire reaction performance:

B-s2,d0, according to the standard EN 13501-1+A1: 2013

only valid for the following configurations:

Configuration	Declared organic content (1)	Declared flame retardant content (1)	Class according to EN 13501-1
Adhesives: - PARA-THERM CIMENT CSE - PARA-THERM POUDRE 3C - PARA-THERM POUDRE 3C+ - PARA-THERM POUDRE CSE - PARA-THERM POUDRE GC - MOUSSE PU COLLAGE ISOLANTS CROMOLOGY SERVICES Insulation product: EPS panels, Euroclass E, thickness ≤ 300 mm, density ≤ 20 kg/m³ Base coat: PARA-THERM CF PATE SE • Mesh: - R 131 A 101 C+ - R 131 A 102 C+ - SSA-1363 F+ Key coat: PARA-THERM RÉGUL Finishing coats: - PARA-THERM CF RIBBÉ G - PARA-THERM CF RIBBÉ M - PARA-THERM CF TALOCHÉ M - PARA-THERM CF TALOCHÉ G - PARA-THERM CF ROULÉ - PARA-THERM CF SILOXANE TALOCHÉ - PARA-THERM CF SILOXANE TALOCHÉ - PARA-THERM CF SILOXANE RIBBÉ - RIV-O-LAND P - RIV-O-LAND M	Base coat: 8.8% Key coat: 13.3% Finishing coats: 7.3 to 14.6%	Base coat: 18.1% Key coat: 0.0% Finishing coats: ≤ 18.3%	B-s2,d0

⁽¹⁾ Percentage declared by the Manufacturer, relative to the dried weight of the component as delivered.

<u>Use category</u>: External insulation of buildings' walls

<u>Particular conditions applicable to the use of the product</u>:

Application on vertical walls of masonry or concrete